CABLE TERMINATOR WALLPLATE

Field terminate audio video cables for TV/monitor and audio speaker cable extension











WP-A (Front)

WP-VGA (Front)

WP-CV (Front)

Features & Applications

The Cable Terminator Wallplate connects a television/monitor and stereo speakers to video and audio distribution wiring within a wall. It can be used to connect VGA video, composite video or S-Video televisions/monitors to home entertainment systems, cable television boxes, DVD players, etc. The cable terminator wallplate features set-screw terminal slots that accommodate straight routing of the wires for easy, clean connections.

- The wallplate is available in five models:
 - VGA
 - VGA and Stereo Audio
 - Stereo Audio
 - VGA and Composite Video
 - S-Video, Composite Video and Stereo Audio
- No special tools needed. Terminal block design with set screws provides reliable electrical connections.
- Connectors on the back of the wallplate are specially oriented to permit an almost straight routing of the wires.
- Proper installation is practically foolproof. The terminal block area is clearly marked, and a wiring diagram is included.
- Eliminates cable clutter.

Specifications

Compatibility

- WP-VGA: supports any VGA monitor.
- WP-AV: supports any VGA monitor and unbalanced stereo
- WP-A: Supports unbalanced stereo audio.
- WP-CV: supports any VGA or composite video TV/monitor.
- WP-CSA: supports any S-Video or composite video TV/ monitor and unbalanced stereo audio.

Connectors

- WP-VGA: one female 15-pin HD connector.
- WP-AV: one female 15-pin HD connector, one 3.5mm stereo
- WP-A: one 3.5mm stereo audio jack.
- WP-CV: one female 15-pin HD connector, one RCA composite video jack.
- WP-CSA: one female 4-pin miniDIN connector, one RCA. composite video jack, one set (right and left) of RCA audio jacks.

- Internal cable connectors:
 - WP-VGA, WP-AV and WP-CV: terminal block, 2x12 positions.
 - WP-CSA: terminal block, 1x12 positions.
 - WP-A: terminal block, 1x6 positions.
- Cable routing: straight.

Wallplate

- Standard single-wide wallplate.
- Size (WxDxH): 2.8x1.1x4.5 inches.
- The terminal block extends 0.65 inches for WP-AV, WP-VGA, WP-A and WP-CV, and one inch for WP-CSA from the back of wallplate.
- The connectors protrude less than 1/2 inch from front of
- 3.25 inches between two mounting holes.

Electrical Box

Single gang, standard US.

Regulatory Approvals

CE, RoHS



WP-AV (Back)



